

# Easy Up 5 Picking

## Standard equipment

- 2WD traction, DC electric motors and electromagnetic brakes
- Swivel caster interlock for straight line driving
- Selector for 3 different proportional speed
- Non marking tires
- Double material tray, non-slip, adjustable and fixed
- Double door access gate with spring-lock
- Control box on platform IP65, with proportional joystick and emergency stop
- Ground control panel with key switch
- Inclinomometer with audible/visual alarm and motion cut out
- Load sensor with audible/visual alarm and motion cut out
- Electrical scissor protection
- Pothole protection
- Audible motion alarm, horn and flashing beacon
- Low battery alert
- Battery charger with automatic switch-off
- Manual emergency lowering device
- Cylinder holding valve

## Benefits

- ✓ Higher productivity thanks to the powered traction also allowed at full height
- ✓ Excellent manoeuvrability, safe, quick and precise positioning in very congested sites
- ✓ Large material tray, non-slip, adjustable in 8 positions
- ✓ It can be driven through standard doorways and carried in passenger elevators
- ✓ Ease of loading either by ramps, forklift pockets and crane lifting points
- ✓ Light and handy, with non marking tires, ideal for delicate and/or raised access flooring
- ✓ Outstanding battery capacity provides long endurance
- ✓ Battery charger with automatic compensation charge for long periods of inactivity. Just leave it ON.
- ✓ Emergency lowering device easy and quick to operate

### EASY UP 5 Picking

|  |         |            |
|--|---------|------------|
| Number of scissors                     |         | 3          |
| A                                      | mm      | 3200       |
| B                                      | mm      | 5200       |
| C                                      | mm      | 25         |
| D                                      | mm      | 1820       |
| E                                      | mm      | 710        |
| Platform dimensions                    | mm      | 700x620    |
| Material tray dimensions               | mm      | 500x620    |
| Platform capacity (including 1 person) | kg      | 120        |
| Material tray capacity                 | kg      | 80         |
| Total capacity (including 1 person)    | kg      | 200        |
| Electric motor (power pack)            | kW      | 2          |
| Electric drive motors                  | V/kW    | 24/1       |
| Battery                                | V/Ah    | 2 x 12/105 |
| Battery charger                        | V       | 230        |
| Oil tank capacity                      | l       | 2          |
| Lifting time                           | s       | 17/20      |
| Max side/longitudinal tilt angle       | degrees | 1.5/2.5    |
| Gradeability                           | %       | 25         |
| Traction speed                         | km/h    | 0 - 4      |
| Safety traction speed                  | km/h    | 0.6        |
| Internal turning radius                | m       | 0          |
| External turning radius                | m       | 1.25       |
| Total weight                           | kg      | 585        |



Large material tray, non-slip, adjustable in 8 positions.



Proper and ergonomic components disposition for easier and faster maintenance task.



Sturdy IP65, simple and intuitive control box.



Swivel castor interlock for straight line driving.



Ground control panel, intuitive and well protected from accidental bumps.



### EASY UP 5 Picking

